



DOMO SERIES

The DOMO Series is a stainless steel submersible pump with multiple impellers and float switch for clean water use. This pump is capable of a max head rating of 40m, which is suitable for intank installation for double storey homes. The DOMO Series can also be used with electronic controller for pressure system applications.

FEATURES

- Light-weight design.
- 304SS body casing.
- Automatic float key switch.
- Built-in motor protection.
- Top-mounted discharge.

APPLICATIONS

- Domestic / residential.
- Garden water supply.

PERFORMANCE TABLE

Model	Power	
	Watts	Voltage
DOMO 1000/4	1000	240V
	Max Flow	Max Head
	Lpm	(M)
	92	40
	Discharge	
	(mm)	25



SF & SH SERIES

The SF and SH Series of commercial quality drainer pumps are suited for multiple applications. Heavy duty, rugged construction assures a long and economical operational life. These 'clean water' transfer pumps with heads to 25m and flows to 360lpm, are ideal for pumping dirty water containing light dirt etc. in suspension.

FEATURES

- Rugged & light-weight.
- Stainless steel motor casing.
- Automatic or manual operation.
- Handles 6mm spherical solids.
- Double mechanical seal plus shaft seal.
- Built-in motor protection.
- Semi-open impeller (bronze).

APPLICATIONS

- Civil engineering & construction.
- Industrial / commercial.
- Fountains & water features.
- General de-watering.

PERFORMANCE TABLE

Model	Power	
	kW	Voltage
SFA-0512N	0.40	240V
SF-132AN	0.75	415V
SHA-112N	0.75	240V
	Max Flow	Max Head
	Lpm	(M)
SFA-0512N	220	10
SF-132AN	350	16
SHA-112N	240	20
	Discharge	Spherical solid
	(mm)	handling (mm)
SFA-0512N	50	4
SF-132AN	50	6
SHA-112N	40	4

Note: "A" = indicates automatic operation.